Type of Document Heat Treat Inspection Report Issued By (Name, Phone) Approved By (Name, Phone) Approved By (Name, Phone) Mr.PRATAP GHORPADE This document shall not be reproduced except in full without the consent of the Quality Assurance Department. Customer Rear Axie Shaft Process HARDENNG & TEMPERN Component weight per Pc. Processed Qiv. Surface Hardness Specification: Sample-2 So - S8 HRC Sample-2 Core Hardness Specification: S0 - S8 HRC Sample-2 Sample-1 57 Sample-2 57 Sample-2 57 Sample-2 58 Core Hardness Results (HRC) Sample-1 57 Sample-2 58 Sample-2 57 Sample-2 58 Sample-1 56 Sample-2	(A)	HIC	GHTEMP FUR		TED				
Type of Document Heat Treat Inspection Report Issued By (Name, Phone) Approved By (Name, Phone) Approved By (Name, Phone) Mr.PRATAP GHORPADE This document shall not be reproduced except in full without the consent of the Quality Assurance Department. Customer Rear Axie Shaft Process HARDENNG & TEMPERN Component weight per Pc. Processed Qiv. Surface Hardness Specification: Sample-2 So - S8 HRC Sample-2 Core Hardness Specification: S0 - S8 HRC Sample-2 Sample-1 57 Sample-2 57 Sample-2 57 Sample-2 58 Core Hardness Results (HRC) Sample-1 57 Sample-2 58 Sample-2 57 Sample-2 58 Sample-1 56 Sample-2		MMERCIAL	HEAT TREAT	MENT DIVISI	ON BANGAL	ORE			
Type of Document Heat Treat Inspection Report Issue Date 1406/2010 Issue Date 1406/2010 Issue Date 1406/2010 Issue Date 1406/2010 Material 154/P Process HARDENING & TEMPERR Custom er Fart Name Rear Axie Shaft Portesson (Irreace Component weight per Pc. Process Surface Hardness Specification: NA (Check For Reference Only) Sample-1 Surface Hardness Specification: NA (Check For Reference Only) 19 Customer 40Cr4P Procession Trail Conducted Induction Harden Surface Hardness Specification: NA (Check For Reference Only) 19 Customer 40Cr4P Procession Trail Conducted Induction Harden Surface Hardness Specification: NA (Check For Reference Only) 19 Customer 40Cr4P Procession Fart Name Procession Frial Conducted Induction Harden Surface Hardness Specification: NA (Check For Reference Only) 19 Customer 40Cr4P Procession Frial Conducted Induction Harden Surface Hardness Specification: So ~ 58 HC Sample-1 Surface Hardness Specification: So ~ 58 HC Sample-1 Sample	Name of Document			Trial Conducted Induction Harden & Pvro Tempering					
Issued By:(Name, Phone) Mr.PRATAP GHORPADE This document shall not be reproduced except in full without the consent of the Cuality Assurance Department. Customer Rear Axie Shaft Material 1441P Process Trial Conducted Induction Harden Starge Number / Furnace Serial No. / IR.No. Core hardness Specification: NA (Check For Reference Only) Smith No. / IR.No. Core Hardness Specification: NA (Check For Reference Only) MICROSTRUCTURE AT 200X Customer MicROSTRUCTURE AT 200X Customer Order Hardness Results (HRC) Surface Hardness Specification: NA (Check For Reference Only) 9 Customer MicROSTRUCTURE AT 200X Customer Order Hardness Results (HRC) Surface Hardness Specification: NA (Check For Reference Only) MICROSTRUCTURE AT 200X Customer Order Hardness Results (HRC) Surface Hardness Specification: NA (Check For Reference Only) Part Name Rear Axle Shaft Processed Qiv, 3 Material OCrep Hardness Results (HRC) Surface Hardness Results (HRC) Processed Qiv, 3 Surface Hardness Specification: So - S8 HRC Sample-1 Surface Hardness Results (HRC) Processed Qiv, 3 Surface Hardness Results (HRC) Sample-1 Surface Hardness Results (HRC) <td< td=""><td colspan="3">Type of Document</td><td colspan="5"></td></td<>	Type of Document								
Approved By (Name, Phone) Mr. PRATAP GHORPADE This document shall not be reproduced except in full whout the consent of the Oulity Assurance Department. Customer Material Process Hardness Specification: S0 - 58 HRC Core Hardness Specification: NA (Check For Reference Only) MicROSTRUCTURE AT 200X Component Weight per Pe. Surface Hardness Specification: SA Core Hardness Specification: SA Surface Hardness Specification: SA Core Hardness Specification: SA Surface Hardness Specification: SA Component Weight per Pe. Surface Hardness Specification: SA Component Weight per Pe. Surface Hardness Specification: SA Core Hardness Specification:	Issue Date								
This document shall not be reproduced except in full without the consent of the Quality Assurance Department. Customer Rear Axie Shaft Material 1441P Process Trial Conducted Induction Harden Charge Number / Furnace Serial No. / LRNo. Component weight per Pc. Processed Qry. 2 Nos. Surface Hardness Specification: Surface Hardness Results (HRC) Sample-1 So - 68 HRC Sample-1 56 57 59 Indication Core Hardness Specification: NA (Check For Reference Only) 19 20 Indication MICROSTRUCTUREAT 200X Wicrosses Customer Hardness Specification: NA (Check For Reference Only) 19 20 Indication Material 40Cr4P Part Name Rear Axle Shaft Processe HARDENING & TEMPERIX Comments Trial Conducted Induction Harden Charge Number / Furnace Part Name Rear Axle Shaft Surface Hardness Specification: NA (Check For Reference Only) Serial No. / I.R.No. Trial Conducted Induction Harden Surface Hardness Specification: So - S8 HRC Sample-1 56 56 55 55 55 55	Issued By:(Name, Phone)								
Customer Part Name Part Name Part Xie Shaft Material 1941 Part Name Part Name Part Xie Shaft Process HARDENING & TEMPERIN Comments Trial Conducted Induction Harden Component weight per Pc. Processed City. 2 Nos. Surface Hardness Specification: S0 - 58 HRC Surface Hardness Specification: NA Core Hardness Specification: NA (Check For Reference Only) Customer Material 40Cr4P Part Name Part Name Rear Axie Shaft Component weight per Pc. Part Name Rear Axie Shaft Process HARDENING & TEMPERIN Comments Customer Material 40Cr4P Process HARDENING & TEMPERIN Comments Surface Hardness Specification: S0 - 58 HRC Surface Hardness Specification: NA Core Hardness Specification: NA Check For Reference Only) Customer Material 40Cr4P Part Name Rear Axie Shaft Process HARDENING & TEMPERIN Comments Charge Number / Furnace Surface Hardness Specification: S0 - 58 HRC	Approved By:(Name, Phone)								
Material 1641P Process HARDENING & TEMPERIC Comments Charge Number / Furnace Component weight per Pc. Processed Qiy. 2 Nos. Processed Qiy. 2 Nos. Core Hardness Specification: NA (Check For Reference Only) 19 20 MICROSTRUCTURE AT 200X Customer Material 40Cr4P Part Name Rear Axle Shaft Material 40Cr4P Part Name Trial Conducted Induction Harden Serial No. / LR.No. Surface Hardness Results (HRC) Simple-2 56 56 56 5 Core hardness Specification: NA (Check For Reference Only) 20 MICROSTRUCTURE AT 200X Customer Article Part Name Rear Axle Shaft Material 40Cr4P Part Name Rear Axle Shaft Material 56 56 56 5 Core Hardness Specification: NA (Check For Reference Only) 22 22 22 1 MICROSTRUCTURE AT 200X Processe Care Specification: NA (Check For Reference Only) 22 22 22 1 MICROSTRUCTURE AT 200X				thout the consent of the Quality Assurance Department.					
Process HARDENING & TEMPERIC Comments Trial Conducted Induction Harden Charge Number / Furnace Specification: 50 ~ 58 HRC Sample-1 57 58 59 50 50 50 50 50 50 50 50 50 50 50 50 50	Customer			Part Name Rear Axle Shaft					
Charge Number / Furnace Serial No. / I.R.No. Component weight per PC. Surface Hardness Specification: S0 ~ 58 HRC Core Hardness Specification: NA (Check For Reference Only) Customer Material Material Surface Hardness Specification: Surface Hardness Results (HRC) Customer Material Surface Hardness Specification: Surface Hardness Results (HRC) Customer Material Surface Hardness Specification: Surface Hardness Results (HRC) Customer Material Surface Hardness Specification: Surface Hardness Results (HRC) Surface Hardness Results (HRC) Customer Material Surface Hardness Specification: Surface Hardn	Material					1			
Component weight par Pc. Processed Qty. 2 Nos. Surface Hardness Specification: 50 ~ 58 HRC Sample-1 57 58 59 Core Hardness Specification: Sample-2 56 57 59 1 Core Hardness Specification: NA (Check For Reference Only) Core Hardness Results (HRC) 19 20 MICROSTRUCTURE AT 200X	Process	HARDENING & TEMPERIN		Comments		Trial Conducted Induction Harden			
Surface Hardness Specification: 50 ~ 58 HRC Surface Hardness Results (HRC) Surface Hardness Specification: NA (Check For Reference Only) Core Hardness Results (HRC) Core Hardness Specification: NA (Check For Reference Only) Core Hardness Results (HRC) MICROSTRUCTURE AT 200X Trial Conducted Induction Harden Serial No. /1.RNo. Process Part Name Rear Axie Shaft Part Name Rear Axie Shaft Part Name Part Name Part Name Part Axie Shaft Part Name Part Axie Shaft Process Printage Res Axie Shaft Surface Hardness Specification: Surface Hardness Resuits (HRC) <th colspa<="" td=""><td>Charge Number / Furnace</td><td colspan="2"></td><td colspan="2">Serial No. / I.R.No.</td><td colspan="3"></td></th>	<td>Charge Number / Furnace</td> <td colspan="2"></td> <td colspan="2">Serial No. / I.R.No.</td> <td colspan="3"></td>	Charge Number / Furnace			Serial No. / I.R.No.				
Surface Hardness Specification: S0 - 55 HRC Surface Hardness Results (HRC) Sample-1 57 58 59 1 Core Hardness Specification: NA (Check For Reference Only) 19 20 1 MICROSTRUCTURE AT 200X MICROSTRUCTURE AT 200X Core Hardness Results (HRC) MICROSTRUCTURE AT 200X Customer Material Part Name Rear Axle Shaft Mart Name Part Name Rear Axle Shaft Material 40Cr4P Part Name Rear Axle Shaft Surface Hardness Specification: Na Part Name Rear Axle Shaft Surface Hardness Specification: Na Part Name Rear Axle Shaft <	Component weight per Pc.			Processed Qty.		2 Nos.			
Surface Hardness Specification: S0 - 55 HRC Surface Hardness Results (HRC) Sample-1 57 58 59 1 Core Hardness Specification: NA (Check For Reference Only) 19 20 1 MICROSTRUCTURE AT 200X MICROSTRUCTURE AT 200X Core Hardness Results (HRC) MICROSTRUCTURE AT 200X Customer Material Part Name Rear Axle Shaft Mart Name Part Name Rear Axle Shaft Material 40Cr4P Part Name Rear Axle Shaft Surface Hardness Specification: Na Part Name Rear Axle Shaft Surface Hardness Specification: Na Part Name Rear Axle Shaft <		•		PYRO '	TEMPERED A	T 195°C For	30Min.		
50 - 58 HRC Sample-1 Sample-2 Sample-2 56 57 59 59 Core Hardness Specification: NA (Check For Reference Only) 19 20 MICROST RUCTURE AT 200X MICROST RUCTURE AT 200X Customer Material 40Cr4P Part Name Part Name Rear Axie Shaft Trial Conducted Induction Harden Charge Number / Furnace Serial No. / LR No. Core Hardness Specification: Sor - 58 HRC Surface Hardness Specification: So - 58 HRC Surface Hardness Specification: Sor - 58 HRC Surface Hardness Specification: NA (Check For Reference Only) 2 22 MICROSTRUCTURE AT 200X	50 ~ 58 HRC								
Sumple-2 56 57 59 Core Hardness Specification: NA (Check For Reference Only) 19 20 Core Hardness Results (HRC) MICROSTRUCTURE AT 200X Customer Mame Rear Axle Shaft Material 40Cr4P Part Name Rear Axle Shaft Process HARDENING & TEMPERK Trial Conducted Induction Harden Surface Hardness Specification: S0 - 58 HRC Sample-1 56 56 Surface Hardness Specification: S0 - 58 HRC Surface Hardness Results (HRC) Sample-1 Surface Hardness Specification: S0 - 58 HRC Core Hardness Results (HRC) Sample-1 Surface Hardness Specification: S0 - 58 HRC Core Hardness Results (HRC) Sample-2 Surface Hardness Specification: NA (Check For Reference Orly) Core Hardness Results (HRC) Sample-2 MICROSTRUCTURE AT 200X MICROSTRUCTURE AT 200X				Suri	ace Harones	ss Results ((HRC)	-	
Core Hardness Results (HRC) 19 20 MICROSTRUCTURE AT 200X MICROSTRUCTURE AT 200X Image: Customer Material Part Name Rear Axle Shaft Part Name Rear Axle Shaft Process HARDENING & TEMPERI Trial Conducted Induction Harden Component weight per Pc. Processed QLY, 3 Nos. Processed QLY, 3 Nos. Surface Hardness Specification: So - 58 HRC Sample-1 56 56 55 Core Hardness Results (HRC) 22 22 22 22 22 MICROSTRUCTURE AT 200X MICROSTRUCTURE AT 200X MICROSTRUCTURE AT 200X DISPO SITIO N.: QA PREPARED BY:			Sample-1	57	58	59			
Core Hardness Results (HRC) 19 20 MICROSTRUCTURE AT 200X MICROSTRUCTURE AT 200X Image: Customer Material Part Name Rear Axle Shaft Part Name Rear Axle Shaft Process HARDENING & TEMPERI Trial Conducted Induction Harden Component weight per Pc. Processed QLY, 3 Nos. Processed QLY, 3 Nos. Surface Hardness Specification: So - 58 HRC Sample-1 56 56 55 Core Hardness Results (HRC) 22 22 22 22 22 MICROSTRUCTURE AT 200X MICROSTRUCTURE AT 200X MICROSTRUCTURE AT 200X DISPO SITIO N.: QA PREPARED BY:			Sample-2	56	57	59			
Ig 20 MICROSTRUCTURE AT 200X MICROSTRUCTURE AT 200X Quite of the second secon									
MICROSTRUCTURE AT 200X MICROSTRUCTURE AT 200X Customer Part Name Rear Axle Shaft Material 40Cr4P Part Name Rear Axle Shaft Trial Conducted Induction Harden Component weight per Pc. Processed Qty. Surface Hardness Specification: Surface Hardness Specification: Surface Hardness Specification: Sourface Hardness Specification: NA Core Hardness Results (HRC) 22 MICROSTRUCTURE AT 200X	-					Results (H			
Customer 40Cr4P Part Name Rear Axle Shaft Material 40Cr4P Part Number Part Number Process HARDENING & TEMPERI Comments Trial Conducted Induction Harden Charge Number / Furnace Serial No. / I.R.No. Serial No. / I.R.No. Serial No. / I.R.No. Component weight per Pc. Processed Qty. 3 Nos. Process Results (HRC) Surface Hardness Specification: Surface Hardness Results (HRC) Sample-1 56 56 55 5 5 55 55 55 55 55 5 56 56 56	(Check For Reference On	iy)	19	20					
Material 40Cr4P Part Number Process HARDENING & TEMPERIN Comments Trial Conducted Induction Harden Charge Number / Furnace Serial No. / I.R.No. Processed Qty. 3 Nos. Component weight per Pc. Processed Qty. 3 Nos. Processed Qty. 3 Nos. Surface Hardness Specification: So ~ 58 HRC Sample-1 56 56 55 Core Hardness Specification: NA (Check For Reference Only) Core Hardness Results (HRC) 22 22 22 22 22 MICROSTRUCTURE AT 200X MICROSTRUCTURE AT 200X MICROSTRUCTURE AT 200X Sample-1 50	MICROSTRUCTURE AT 200X								
Material 40Cr4P Part Number Process HARDENING & TEMPERIN Comments Trial Conducted Induction Harden Charge Number / Furnace Serial No. / I.R.No. Processed Qty. 3 Nos. Component weight per Pc. Processed Qty. 3 Nos. Processed Qty. 3 Nos. Surface Hardness Specification: So ~ 58 HRC Sample-1 56 56 55 Core Hardness Specification: NA (Check For Reference Only) Core Hardness Results (HRC) 22 22 22 22 22 MICROSTRUCTURE AT 200X MICROSTRUCTURE AT 200X MICROSTRUCTURE AT 200X Sample-1 50									
Material 40Cr4P Part Number Process HARDENING & TEMPERIN Comments Trial Conducted Induction Harden Charge Number / Furnace Serial No. / I.R.No. Processed Qty. 3 Nos. Component weight per Pc. Processed Qty. 3 Nos. Processed Qty. 3 Nos. Surface Hardness Specification: So ~ 58 HRC Sample-1 56 56 55 Core Hardness Specification: NA (Check For Reference Only) Core Hardness Results (HRC) 22 22 22 22 22 MICROSTRUCTURE AT 200X MICROSTRUCTURE AT 200X MICROSTRUCTURE AT 200X Sample-1 50	Customor			Port Nom o		Boor Aylo S	Shoft		
Process HARDENING & TEMPERIN Comments Trial Conducted Induction Harden Charge Number / Furnace Serial No. / I.R.No. Processed Cty. 3 Nos. Component weight per Pc. Processed Cty. 3 Nos. Surface Hardness Specification: 50 ~ 58 HRC Surface Hardness Results (HRC) So ~ 58 HRC Sample-1 56 56 55 Core Hardness Specification: NA (Check For Reference Only) 22 22 22 22		40Cr4P				Neal Axie	Shart		
Charge Number / Furnace Serial No. / I.R.No. Component weight per Pc. Processed Qty. 3 Nos. Surface Hardness Specification: 50 ~ 58 HRC Surface Hardness Results (HRC) So ~ 58 HRC Sample-1 56 56 55 Core Hardness Specification: NA (Check For Reference Only) Core Hardness Results (HRC) 22 22 22 22 MICROSTRUCTURE AT 200X MICROSTRUCTURE AT 200X DISPO SITIO N : QA PREPARED BY:						Trial Condu	usted Indust	ion Hordon	
Component weight per Pc. Processed Qty. 3 Nos. Surface Hardness Specification: 50 ~ 58 HRC Surface Hardness Specification: NA (Check For Reference Only) Core Hardness Results (HRC) Core Hardness Specification: NA (Check For Reference Only) MICROSTRUCTURE AT 200X MICROSTRUCTURE AT 200X DISPO SITIO N: QA						Thai Conu		Ion naruen	
Surface Hardness Specification: Surface Hardness Results (HRC) 50 ~ 58 HRC Sam ple-1 56 56 56 Core Hardness Specification: NA (Check For Reference Only) Core Hardness Results (HRC) Core Hardness Results (HRC) Z2 22 22 22 22 22 MICROSTRUCTURE AT 200X MICROSTRUCTURE AT 200X DISPO SITIO N: QA						2 No.0			
Surface Hardness Specification: Surface Hardness Results (HRC) Sam ple-1 56 56 56 Sam ple-2 56 55 55 1 Core Hardness Specification: NA (Check For Reference Only) Core Hardness Results (HRC) 1 1 VICROSTRUCTURE AT 200X MICROSTRUCTURE AT 200X MICROSTRUCTURE AT 200X 1 1 DISPO SITIO N: Sufface Hardness Results (HRC) Sufface Hardness Results (HRC) 1 1 DISPO SITIO N: Sufface Hardness Results (HRC) Sufface Hardness Results (HRC) 1 1	Component weight per Pc.								
Solution indication: Sam ple-1 56 56 56 Sam ple-2 56 55 55 Core Hardness Specification: NA (Check For Reference Only) Core Hardness Results (HRC) Z2 22 22 22									
Sample -2 56 55 55 Core Hardness Specification: NA (Check For Reference Only) 22 22 22 MICROSTRUCTURE AT 200X				Surf	ace Hardne	ss Results ((HRC)		
Sample-2 56 55 Core Hardness Specification: NA (Check For Reference Only) 22 22 22 MICROSTRUCTURE AT 200X			Sample-1	56	56	56			
Core Hardness Results (HRC) 22 22 22 22 MICROSTRUCTURE AT 200X Image: Second Secon					55				
(Check For Reference Only) 22 22 22 MICROSTRUCTURE AT 200X			Sample-2						
MICROSTRUCTURE AT 200X Image: State of the s				Co	re Hardness	s Results (H	RC)		
DISPOSITION:	(Check For Reference On	ly)	22	22	22				
DISPOSITION:		N	ICROSTRUC	TURE AT 200	X				
QA	212	No.		×					
ISSUE DATE: 14/06/2010 APPROVED BY: PRATAP GHORPADE									
	DISPO SITION:			QA					
	DISPOSITION: ISSUE DATE: 14/06/2010			QA			9 GHORPADE		